

STANDARD MANIFOLD LINE MOUNT BODIES

Ordering Code: ML-11A3-X-Y 05-Z			Ordering Code:				
		ML-11A3-G03A-A05-CB3H ML-11A3-G03A-A05-CO20					
<u>G 3/8"</u> <u>G </u>							
				TECHNICAL DATA			
				Aluminum Body Pressure Rating: 210 bar Ductile Iron Body Pressure Rating: 350 bar			
				Cavity: Refer to 11A3 * Refer to Winner Cartridge Valves Catalog.			
				Aluminum 0.45 kg(WITHOUT VALVES)			
			Ductile Iron 1.04 kg(WITHOUT VALVES)				
UNIT:mm $ \oplus \ \buildrel \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \$				* If you need the special specification. Please contact us.			
			x	PORT SIZE			
				PORTS	PORTS		
			1,2	3,4			
		G03A	G 3/8"	G 1/4"			
Y	BODY MATERIAL		Z	CARTRIDGE VALVES SELECTION			
Α	HIGH-STRENGTH ALUMINUM			WITHOUT VALVE			
S	DUCTILE IRON		CB3H	CB11A33HL (3:1 , 280bar)			
			CO20	CO11A3020N (60LPM , 2.0bar)			
Rev.1206			The selection is only example. Please refer to Winner Cartridge Program and to select the appropriate valves and maniflods assembly in accordance with request function (flow \ pressure \ etc.)				