

STANDARD MANIFOLD LINE MOUNT BODIES

| Ordering Code: ML-162A2-X-Y01-Z | | | | | | | |
|---|------------------------|--|---|-----------------------------------|------|-------|------------|
| tic c c c c c c c c c c c c c c c c c c | | | | | | | |
| | | | 1 | | | | |
| Image: Constraint of the second se | | | TECHNICAL DATA Aluminum Body Pressure Rating: 210 bar Ductile Iron 250 h ar | | | | |
| | | | Body Pressure Rating: 350 bar | | | | |
| | | | Cavity: Refer to 162A2 * Refer to Winner Cartridge Valves Catalog. | | | | |
| | | | Aluminum 0.12 kg(WITHOUT VALVES) | | | | |
| | | | Ductile | tile Iron 0.35 kg(WITHOUT VALVES) | | | |
| UNIT:mm $	Geta$ | | | * If you need the special specification. Please contact us. | | | | |
| | | | x | PORT SIZE | | | |
| | | | | PC | ORT | PORT | |
| | | | | | 1 | 2 | |
| | | | G02 | G1/4" | | G1/4" | |
| | | | G03 | G3/8" | | G3/8" | |
| | | | S06 | SA | AE 6 | SAE 6 | |
| Y | BODY MATERIAL | | Z | CARTRIDGE VALVES SELECTION | | | |
| Α | HIGH-STRENGTH ALUMINUM | | | WITHOUT VALVE | | | |
| S | DUCTILE IRON | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| Rev 1405 | | | | | | | M 162A 201 |