





ISO 03 COVER MANIFOLD










Υ	SELECTION FOR FLOW CONTRO (REFER TO PFC13A-X-Y-Z)	L VALVE	
13A2	CAVITY ONLY (WITHOUT VALVE)		
PFC03	PFC13A2D0030N(0.3~3LPM)		
PFC06	PFC13A2D0060N(0.4~6LPM)		
PFC14	PFC13A2D0140N(0.6~14LPM)		
PFC28	PFC13A2D0280N(0.8~28LPM)		
PFC40	PFC13A2D0400N(1.0~40LPM)		
COIL MUST BE ORDERED SEPARATELY (REFER TO EC-19A-X-Y-Z)			



TECHNICAL DATA

Aluminum Body Pressure Rating: 250 bar

Ductile Iron

Body Pressure Rating: 350 bar

Rated flow: 40 I/min

Cartridge Valve: Refer to LP11A-XI-YI-ZI PFC13A-XI-YI-ZI

* Refer to Winner Cartridge Valves Catalog.

Aluminum	0.63 kg(WITHOUT VALVES) 1.2 kg(INCLUDE VALVES ,WITHOUT COIL)	

* If you need the special specification. Please contact us.

X	SELECTION FOR COMPENSATOR		
11A3	CAVITY ONLY(WITHOUT VALVE)		
LP140	LP11A30140N(60LPM,14.0bar)		

Z	BODY MATERIAL	
Α	HIGH-STRENGTH ALUMINUM	

Rev.170328 M.EPX.372